





订货引导  
A CT A - B2 - D1 - L2  
大类别 系列 1 材质 2 外径 3 长度  
请参考系列代码来选择型式和参数进行订购。

| 代码      | 形状 | 磁力方向 | 材质 ①  | 表面处理 | 耐热温度  |
|---------|----|------|-------|------|-------|
| ACTA-B2 | 圆形 | 轴向   | 钕磁铁   | 镀锌   | 80°C  |
| ACTA-B3 |    |      | 强力钕磁铁 |      | 60°C  |
| ACTA-B4 |    |      | 耐热钕磁铁 |      | 150°C |
| ACTA-B1 |    |      | 钴磁铁   | -    | 200°C |



磁力方向:轴向



视角标准:第一视角

| 型号                                       |     | L ③ | 吸引力 N(kgf)   |             |             | 表面磁通密度高斯 (G) |           |           |
|------------------------------------------|-----|-----|--------------|-------------|-------------|--------------|-----------|-----------|
| 代码                                       | D ② |     | ACTA-B2/B4   | ACTA-B3     | ACTA-B1     | ACTA-B2/B4   | ACTA-B3   | ACTA-B1   |
| ACTA-B2<br>ACTA-B3<br>ACTA-B4<br>ACTA-B1 | 1   | 2   | 0.05(0.005)  | 0.08(0.008) | -           | 1000~1300    | 1900~2100 | -         |
|                                          |     | 3   | 0.06(0.006)  | -           | -           | 1100~1400    | -         | -         |
|                                          |     | 5   | 0.07(0.007)  | 0.10(0.01)  | -           | 1200~1500    | 2100~2300 | -         |
|                                          | 2   | 2   | 0.55(0.055)  | 0.77(0.08)  | 0.39(0.04)  | 2300~2600    | 3500~3700 | 2000~2200 |
|                                          |     | 3   | 0.65(0.065)  | 0.90(0.09)  | 0.49(0.05)  | 3000~3300    | 3700~3900 | 2600~2800 |
|                                          |     | 4   | 0.70(0.070)  | 0.93(0.09)  | -           | 3200~3600    | 3700~3900 | -         |
|                                          | 3   | 5   | 0.75(0.075)  | 1.01(0.10)  | 0.49(0.05)  | 3000~3300    | 4100~4300 | 2600~2800 |
|                                          |     | 1   | 1.05(0.105)  | 1.39(0.14)  | -           | 1900~2400    | 2700~2900 | -         |
|                                          |     | 2   | 1.55(0.155)  | 2.05(0.21)  | 1.08(0.11)  | 3000~3300    | 3700~4000 | 2600~2800 |
|                                          |     | 3   | 1.95(0.195)  | 2.55(0.26)  | 1.37(0.14)  | 3200~3500    | 4200~4500 | 2800~3000 |
|                                          |     | 4   | 2.20(0.220)  | 2.93(0.30)  | 1.47(0.15)  | 3300~3600    | 4400~4700 | 2900~3100 |
|                                          |     | 5   | 2.30(0.230)  | 3.06(0.31)  | 1.57(0.16)  | 3400~3700    | 4500~4800 | -         |
|                                          | 4   | 6   | 2.80(0.280)  | 3.60(0.37)  | -           | 4000~4300    | 4600~4800 | -         |
|                                          |     | 1   | 1.45(0.145)  | -           | -           | 1900~2200    | -         | -         |
|                                          |     | 2   | 2.80(0.280)  | 3.69(0.38)  | 1.86(0.19)  | 3000~3300    | 4100~4300 | 2600~2800 |
|                                          |     | 3   | 3.80(0.380)  | 4.97(0.51)  | 2.55(0.26)  | 3500~3800    | 4200~4500 | 3100~3300 |
|                                          |     | 4   | 4.30(0.430)  | 5.60(0.57)  | 2.93(0.30)  | 3700~4000    | 4500~4800 | 3200~3400 |
|                                          |     | 5   | 4.65(0.465)  | 6.11(0.62)  | 3.14(0.32)  | 3900~4200    | 4800~5100 | 3300~3600 |
|                                          | 5   | 8   | 6.80(0.680)  | 8.50(0.87)  | -           | 4200~4700    | 5100~5400 | -         |
|                                          |     | 10  | 6.95(0.700)  | 9.05(0.92)  | -           | -            | 5200~5500 | -         |
|                                          | 6   | 1   | 1.43(0.143)  | -           | -           | 1700~2000    | -         | -         |
|                                          |     | 2   | 3.90(0.390)  | 5.10(0.52)  | 2.65(0.27)  | 2900~3200    | 3500~3700 | 2500~2700 |
|                                          |     | 3   | 5.75(0.575)  | 7.51(0.77)  | 3.82(0.39)  | 3700~4000    | 4200~4500 | 3200~3400 |
|                                          |     | 4   | 6.85(0.685)  | 8.92(0.91)  | 4.61(0.47)  | 3900~4200    | 4600~4900 | 3400~3600 |
|                                          | 8   | 5   | 7.60(0.760)  | 9.93(1.01)  | 5.12(0.52)  | 4200~4500    | 4900~5100 | 3500~3800 |
|                                          |     | 6   | 8.10(0.810)  | 10.57(1.08) | 5.39(0.55)  | -            | 5100~5400 | 3600~3800 |
|                                          | 10  | 8   | 8.95(0.900)  | 11.64(1.19) | -           | 4500~4900    | 5200~5500 | -         |
|                                          |     | 10  | 9.80(1.000)  | 12.77(1.30) | -           | 4700~5000    | 5400~5700 | -         |
|                                          | 12  | 2   | 4.95(0.500)  | 6.50(0.66)  | 3.33(0.34)  | 2800~3100    | 3100~3400 | 2400~2600 |
|                                          |     | 3   | 7.60(0.760)  | 9.93(1.01)  | 5.10(0.52)  | 3600~3900    | 4000~4300 | 3100~3300 |
|                                          | 15  | 4   | 9.60(0.960)  | 12.48(1.27) | 6.46(0.66)  | 3800~4100    | 4600~4900 | 3300~3500 |
|                                          |     | 5   | 10.85(1.850) | -           | 7.25(0.74)  | 4200~4500    | -         | 3600~3800 |
|                                          |     | 6   | 11.75(1.750) | 15.29(1.56) | 7.84(0.80)  | 4300~4600    | 5100~5400 | 3700~3900 |
|                                          |     | 8   | 11.80(1.280) | 15.34(1.66) | -           | 4500~4900    | 5400~5600 | -         |
|                                          | 20  | 10  | 11.80(1.180) | 15.39(1.69) | -           | 4700~5000    | 5500~5800 | -         |
|                                          | 25  | 2   | 6.65(0.665)  | -           | 4.41(0.45)  | 2300~2600    | -         | 2000~2200 |
|                                          |     | 3   | 10.75(1.075) | 14.01(1.43) | 7.45(0.76)  | 3100~3400    | 3500~3800 | 2700~2900 |
|                                          |     | 5   | 12.90(1.790) | 23.33(2.38) | 11.96(1.22) | 4100~4400    | 4700~5000 | 3500~3700 |
|                                          |     | 6   | 20.59(2.100) | 26.76(2.73) | -           | 4700~4900    | 5100~5400 | -         |
|                                          |     | 8   | 23.00(2.300) | 29.94(3.06) | 15.39(1.57) | 4500~4800    | 5400~5700 | 3900~4100 |
|                                          | 30  | 10  | 24.00(2.400) | 31.23(3.19) | -           | 4900~5200    | 5600~5900 | -         |
|                                          |     | 2   | 24.00(2.400) | -           | 5.29(0.54)  | 1900~2200    | -         | 1700~1900 |
|                                          |     | 3   | 14.10(1.410) | 18.34(1.87) | 9.41(0.96)  | 2700~3000    | 3100~3400 | 2400~2600 |
|                                          |     | 5   | 24.75(2.475) | 32.23(3.29) | 16.56(1.69) | 3700~4000    | 4300~4600 | 3200~3400 |
|                                          |     | 8   | 34.00(3.400) | -           | 23.03(2.35) | 4600~4900    | -         | 4000~4200 |
|                                          |     | 10  | 38.00(3.800) | 49.43(5.04) | 25.48(2.60) | 4800~5100    | 5500~5800 | 4100~4300 |
|                                          | 40  | 2   | 9.00(0.900)  | -           | 5.98(0.61)  | 1500~1800    | -         | 1250~1500 |
|                                          |     | 3   | 16.45(1.645) | -           | 11.08(1.13) | 2400~2700    | -         | 2100~2300 |
|                                          |     | 5   | 31.15(3.115) | -           | 20.87(2.13) | 3500~3800    | -         | 3000~3200 |
|                                          |     | 8   | 46.50(4.650) | -           | 31.07(3.17) | 4400~4700    | -         | 3800~4000 |
|                                          |     | 10  | 52.70(5.270) | -           | 35.28(3.60) | 4700~5000    | -         | 4000~4200 |
|                                          |     | 2   | 10.55(1.055) | -           | 7.04(0.72)  | 1300~1600    | -         | 1100~1300 |
|                                          | 50  | 3   | 19.55(1.955) | -           | 13.13(1.34) | 2200~2500    | -         | 1950~2100 |
|                                          |     | 5   | 39.55(4.030) | -           | 26.46(2.70) | 3000~3300    | -         | 2600~2800 |
|                                          |     | 8   | 64.35(6.460) | -           | 43.02(4.39) | 4100~4400    | -         | 3500~3700 |
|                                          |     | 10  | 75.85(7.740) | -           | 50.67(5.17) | 4500~4800    | -         | 3800~4000 |
|                                          |     | 3   | 34.32(3.500) | -           | -           | 1600~1900    | -         | -         |
|                                          |     | 10  | 98.06(10.00) | -           | -           | 4100~4400    | -         | -         |

① 吸引力、表面磁通密度是指磁铁单件的值(仅供参考)。