




F674ZZ



订货引导

型号

请参考系列代码来选择型式和参数进行订购。



安装图



视角标准：第一视角

型号	d	D	B	D ₁	C	r ₁ (Min.)	基本额定负载		容许转速 rpm (参考)	安装尺寸		重量g (参考)
							Cr(动) KN	Cor(静) KN		d _b (Min.)	r (Max.)	
F682ZZ	2	5	2.3	6.1	0.6	0.08	169	50	85000	2.7	0.08	0.24
F692ZZ		6	3	7.5	0.8	0.15	330	99	75000	3.0	0.15	0.45
F682AZZ		6	2.6	7.1		0.08	209	74	71000	3.7	0.08	0.42
F692AZZ	2.5	7	3.5	8.5	0.9	0.15	386	129	63000	3.85	0.15	0.68
F673ZZ		6	2.5	7.2	0.6	0.08	242	94	71000	3.6	0.08	0.26
F683ZZ	3	7	3	8.1	0.8	0.1	390	130	63000	3.9	0.1	0.53
F693ZZ		8	4	9.5	0.9		560	180	60000			0.72
F603ZZ		9	5	10.5	1	0.15	571	189	56000	4.2	0.15	1.61
F623ZZ	4	10	4	11.5			640	224	50000			1.8
F674ZZ		7	2.5	8.2	0.6	0.08	222	88	60000	4.6	0.08	0.35
F684ZZ		9		10.3		0.15	640	224	53000	5.0	0.1	1.14
F694ZZ	4	11	4	12.5	1		715	276	48000	5.2	0.15	2
F604ZZ		12		13.5		0.2	957	350				2.57
F624ZZ	5	13	5	15			1310	490	40000	5.6	0.2	3.5
F675ZZ		8	2.5	9.2	0.6	0.08	217	91	53000		0.08	0.4
F685ZZ		11	5	12.5		0.15	715	282	45000	6.2	0.15	2.18
F695ZZ	5	13	4	15	1	0.2	1080	430	43000	6.6	0.2	2.7
F605ZZ		14	5	16			1330	505	40000			3.9
F625ZZ	6	16		18		0.3	1729	675	36000	7.7	0.3	5.52
F676ZZ		10	3	11.2	0.6	0.1	465	196	45000	6.6	0.1	0.74
F686ZZ		13	5	15	1.1	0.15	1080	440	40000	7.0	0.15	3.04
F696ZZ	6	15		17	1.2	0.2	1350	530		7.6	0.2	4.3
F606ZZ		17	6	19		0.3	2190	865	38000	8	0.3	6.5
F626ZZ	8	19		22	1.5		2336	896	32000			9.78
F678ZZ		12	3.5	13.6	0.8	0.1	515	252	40000	8.8	0.1	0.86
F688ZZ		16	5	18	1.1	0.2	1610	715	36000	9.6	0.2	4.47
F698ZZ	8	19	6	22	1.5	0.3	1990	865				8.4
F608ZZ		22	7	25			3350	1400	34000	10	0.3	13
F6700ZZ	10	15	4	16.5	0.8	0.15	855	435	15000	10.3	0.15	2.1
F6800ZZ		19	5	21	1	0.3	1716	840	37000	12		6.1
F6900ZZ		22	6	25	1.5		2695	1273	34000	13.2	0.3	11.1
F6701ZZ	12	18	4	19.5	0.8	0.2	926	530	13000	12.4	0.2	3.4
F6801ZZ		21	5	23	1.1	0.3	1915	1041	33000	14	0.3	7.1
F6901ZZ		24	6	26.5	1.5		2886	1466	31000			13.2
F6702ZZ	15	21	4	22.5	0.8	0.2	937	582	11000	15.4	0.2	3.9
F6802ZZ		24	5	26	1.1	0.3	2073	1253	28000	17	0.3	8.3
F6902ZZ		28	7	30.5	1.5		4321	2259	26000			19.9
F6703ZZ	17	23	4	24.5	0.8	0.2	1000	658	9500	17.4	0.2	4.4
F6803ZZ		26	5	28	1.1	0.3	2233	1456	26000	19	0.3	8.9
F6903ZZ		30	7	32.5	1.5		4588	2565	23000			21.4
F6704ZZ	20	27	4	28.5	0.8	0.2	1041	729	8500	20.4	0.2	6.3
F6804ZZ		32	7	35	1.5		4015	2462	21000	22		19.8
F6904ZZ		37	9	40	2	0.3	6381	3682	19000		0.3	42.8
F6805ZZ	25		7		1.5		4303	2932	18000			26.1
F6905ZZ		42	9	45	2		7001	4540	16000	27		50.2

公差

1Kg f=9.81N

内径d(mm)		内径公差(P6/um)	
超过	到	上偏差	下偏差
0.6	2.5	0	-7
2.5	10	0	-7
10	18	0	-7
18	30	0	-8
30	50	0	-10
50	80	0	-12
80	120	0	-15
120	180	0	-18

外径D(mm)		外径公差(P6/um)	
超过	到	上偏差	下偏差
2.5	6	0	-7
6	18	0	-7
18	30	0	-8
30	50	0	-9
50	80	0	-11
80	120	0	-13
120	150	0	-15
150	180	0	-18
180	250	0	-20
250	315	0	-25