





EPDB - J8D - B1 - 2  
④公称直径 ②主体表面处理 ①主体材质 ③品类  
④公称直径 ②主体表面处理 ①主体材质 ③品类  
 订货引导 (类别) (系列) (类别) (类别)  
 请参考系列代码来选择型号和参数进行订购。

代码	品类③	主体材质①	主体表面处理②	标准号
EPDB-J8D-B1	标准型	SWRH57	镀锌	DIN 127-1987
EPDB-S1W-B1	弹簧垫圈	SUS304	—	



型号		d	D	t	
SWRH57 EPDB-J8D-B1	公称直径④				
	2	2.1	4.4	0.5	
	2.5	2.6	5.1	0.6	
	3	3.1	6.2	0.8	
	4	4.1	7.6	0.9	
	5	5.1	9.2	1.2	
	6	6.1	11.8	1.6	
	8	8.1	14.8	2.0	
	SUS304 EPDB-S1W-B1	10	10.2	18.1	2.2
		12	12.2	21.1	2.5
EPDB-S1W-B1	16	16.2	27.4	3.5	
	20	20.2	33.6	4	
	24	24.5	40.0	5	
	30	30.5	48.2	6	

代码	品类	主体材质①	主体表面处理②	标准号
EPDC-JD	标准型	弹簧钢	镀锌	GB/T 93-1987
EPDC-JE1			发黑	
EPDC-S1W	弹簧垫圈	SUS304	—	
EPDC-S2W		SUS316	—	



型号		d	D	t
弹簧钢 EPDC-JD EPDC-JE1	公称直径④			
	4	4.4	6.8	1.2
	5	5.4	8.2	1.4
	6	6.68	10.08	1.7
	8	8.68	13.08	2.2
	10	10.9	16.4	2.75
	12	12.9	19.4	3.25
	14	14.9	22.5	3.8
	16	16.9	25.5	4.3
	18	19.04	28.44	4.7
	20	21.04	31.44	5.2
	22	23.34	34.74	5.7
	24	25.5	37.9	6.2
	27	28.5	42.7	7.1
	30	31.5	47.1	7.8

型号		d	D	t
SUS304 EPDC-S1W SUS316 EPDC-S2W	公称直径④			
	1.6	1.8	3.4	0.8
	2	2.35	3.51	0.58
	2.5	2.85	4.31	0.73
	3	3.4	5.2	0.9
	4	4.4	6.8	1.2
	5	5.4	8.2	1.4
	6	6.68	10.08	1.7
	8	8.68	13.08	2.2
	10	10.9	16.4	2.75
	12	12.9	19.4	3.25
	14	14.9	22.5	3.8
	16	16.9	25.5	4.3
	18	19.04	28.44	4.7
	20	21.04	31.44	5.2
	22	23.34	34.74	5.7
	24	25.5	37.9	6.2
	27	28.5	42.7	7.1
30	31.5	47.1	7.8	
33	34.7	52.3	8.8	
36	37.7	56.3	9.3	