

A T J U - D4 - L5  
 (大类) (系列) (长度)  
 ① 外径

订货引导 (类别)  
 请参考系列代码来选择型号和参数进行订购。

代码	基准孔	产地	性价比	材质	表面处理	最大压缩量	弹簧常数公差
ATJU	外径基准型	国产	标准型	SWP	发黑	允许位移量L×(20~30)%	±10%





○ D尺寸公差

D	公差
10以下	0 -0.5
12以上	0 -0.8

○ L尺寸公差

L	公差
50以下	±1.5
55以上	±2



视角标准：第一视角

代码	型号		d	压紧长度	F Max.	允许负载 NMax.	弹簧常数 N/mm			
	D ①	L ②								
4	(5)	0.45	2.7	1.5	4.9	3.25				
				3	8.8	2.91				
				15	0.55	5.8	4.5	13.7	3.02	
				20	0.6	8.4	6	17.7	2.93	
				25	0.65	12.4	7.5	22.6	2.99	
				30			9	26.5	2.92	
	(5)	0.6	3.3	1.5	8.8	5.85				
				10	0.7	5.5	3	17.7	5.88	
				15	0.75	7.5	4.5	26.5	5.87	
				25	0.85	13.6	7.5	44.1	5.86	
				30			7.5	44.3	5.89	
				35			8.8	51.6	5.84	
5	(5)	0.6	3.3	1.5	8.8	5.85				
				10	0.7	5.5	3	17.7	5.88	
				15	0.75	7.5	4.5	26.5	5.87	
				25	0.85	13.6	7.5	44.1	5.86	
				30			7.5	44.3	5.89	
				35			8.8	51.6	5.84	
	6	(5)	0.65	3.3	1.5	8.8	5.85			
					10	0.75	5.2	3	17.7	5.88
					15	0.8	6.4	4.5	26.5	5.87
					20	0.9	9.9	6	35.3	5.86
					25			7.5	44.1	
					30			9	53.0	5.87
7		(5)	0.9	17.1	8.8	51.6	5.84			
					8.8	51.9	5.88			
					(5)	0.65	3.3	1.5	8.8	5.85
					10	0.75	5.2	3	17.7	5.88
					15	0.8	6.4	4.5	26.5	5.87
					20	0.9	9.9	6	35.3	5.86
	8	(5)	1	16	10.5	61.8	5.87			
					10.5	61.8				
					12	70.6	5.86			
					11.3	66.7	5.88			
					10	58.8	5.86			
					14.5	85.3				
9		(5)	1.2	39.6	14	82.4	5.87			
					14	82.4				
					15	88.3				
					10	0.9	5.4	3	17.7	5.88
					15	1	8	4.5	26.5	5.87
					20	1.1	11.5	6	35.3	5.86
	10	(5)	1.2	39.6	14	82.4	5.87			
					14	82.4				
					15	88.3				
					10	0.9	5.4	3	17.7	5.88
					15	1.1	8	4.5	26.5	5.87
					20	1.1	11.5	6	35.3	5.86
11		(5)	1.3	24.7	10.5	61.8	5.87			
					10.5	61.8				
					12	70.6	5.86			
					13.5	79.4	5.87			
					15	88.3	5.87			
					16.5	97.1				
	12	(5)	1.4	35	18	105.9	5.86			
					17	100.0				
					19	111.8				
					10	1	5.4	3	17.7	5.88
					15	1.1	7	4.5	26.5	5.87
					20	1.2	9.6	6	35.3	5.86
13		(5)	1.4	18	10.5	61.8	5.87			
					10.5	61.8				
					12	70.6	5.86			
					13.5	79.4	5.87			
					15	88.3	5.87			
					16.5	97.1				
	14	(5)	1.5	25	16.5	97.1				
					18	105.9	5.86			
					17	100.0				
					19	111.8				
					10	1	5.4	3	17.7	5.88
					15	1.1	7	4.5	26.5	5.87
15		(5)	1.6	35	19.5	114.7	5.87			
					21	123.6	5.87			
					21	123.6				
					10	1.1	8	4.5	26.5	5.87
					15	1.2	9.6	6	35.3	5.86
					20	1.3	13.9	9	53.0	5.87
	16	(5)	1.6	45.9	21	123.6	5.87			
					24	141.0	5.86			
					24	141.0				
					10	1.2	9.6	6	35.3	5.86
					15	1.3	13.9	9	53.0	5.87
					20	1.4	18	12	70.6	5.86

代码	型号		d	压紧长度	F Max.	允许负载 NMax.	弹簧常数 N/mm			
	D ①	L ②								
4	10	1.2	6.9	3	17.7	5.88				
				4.5	26.5	5.87				
				20	1.3	9.1	6	35.3	5.86	
				25			7.5	44.1		
				30			9	53.0	5.87	
				35			10.5	61.8		
	5	12	1.5	15.4	12	70.6	5.86			
					13.5	79.4	5.87			
					15	88.3	5.87			
					16.5	97.1				
					18	105.9	5.86			
					19.5	114.7				
6		13	1.7	26.8	18	105.9	5.86			
					19.5	114.7				
					21	123.6	5.87			
					24	141.0	5.86			
					10	1.3	6.2	3	29.4	
					15	1.5	9.3	4.5	44.1	9.78
	7	15	1.6	12.3	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
8		15	1.6	10.4	6	58.8	9.78			
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	9	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
10		15	1.7	10.4	6	58.8	9.78			
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	11	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
12		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	13	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
14		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	15	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
16		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	17	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
18		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	19	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
20		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	21	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
22		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	23	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
24		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	25	15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
26		15	1.7	12.8	6	58.8				
					7.5	73.5				
					9	88.3				
					10.5	103.0				
					12	117.7				
					13.5	132.4	9.79			
	27	15	1.7	12.8	6</					