

订货引导

F GD R - C2 E1 - D3 - T8

1 类别 2 表面处理 3 内径 4 厚度



1 材质

请参考系列代码来选择型号和参数进行订购。


代码	类型	轴固定方式	材质 1	表面处理 2	附件(内六角圆柱头螺钉)
FGDR-C2E1	标准型	分离型	S45C	发黑	2个
FGDR-C2N1				无电解镀锌	
FGDR-S1W			SUS304	-	2个
FGDR-A3W				-	(不锈钢)
FGDR-A3H1			A2017	本色阳极氧化	
FGDR-A3H2				黑色阳极氧化	2个



如防锈有要求, 请优先选用不锈钢材质或无电解镀锌产品。



6.3
其余



视角标准: 第一视角

S45C/SUS304

代码	型号	D 3	T 4	H	M	d	R	W	X	Y	C
FGDR-C2E1 FGDR-C2N1 FGDR-S1W	3	3	16						4.5	2.2	
	4	8	18	M3	3.5	3			5	3	
	5	10	20					1	5.5		
	6	8	20	M4	4.6	3.75			6.5	4	
	8	10	25	M3	3.5	3			8		
	8	12		M4	4.6	3.75					
	10	15		M5	5.6	4.5					
	10	8	30	M6	6.7	6			9	5	
	10	10		M3	3.5	3					
	10	12		M4	4.6	3.75					
	12	12		M5	5.6	4.5					
	12	15		M6	6.7	6					
	12	8	35	M3	3.5	3			10	6	
	12	10	30	M4	4.6	3.75				5	
	12	12		M5	5.6	4.5					
	13	15	35	M6	6.7	6			11	6	0.6
	13	10	30	M4	4.6	3.75			10		
	13	12	34	M5	5.6	4.5			11	5	
	15	15	35	M6	6.7	6					
	15	10	34	M4	4.6	3.75		1.5	11.5	6	
	15	12	35	M5	5.6	4.5			12		
	16	15	40	M6	6.7	6			13	8	
	16	10	35	M5	5.6	4.5			12	6	
	18	15		M6	6.7	6			13	8	
	18	10	40	M5	5.6	4.5			14	7	
	20	15	45	M6	6.7	6			15	8	
	20	10	40	M5	5.6	4.5			14	7	
	25	15	45	M6	6.7	6			15	8	
	25	12		M5	5.6	4.5			17	7	
	30	15	50						18		
	30	20	55	M6	6.7	6			20	10	
	35	15	60	M8	9.1	7					
	40	18	70	M6	6.7	6		2	23	12	1
	50	22	85	M8	9.1	7			26	13	
	60		95	M10	11.1	9	3		32	16	
	80	32	130						37	18	
	100	36	150	M16	18.1	13	5		50	22	1.6
									60	26	

A2017

代码	型号	D 3	T 4	H	M	d	R	W	X	Y	C
FGDR-A3W FGDR-A3H1 FGDR-A3H2	3	3	16						4.5	2.2	
	4	8	18	M3	3.5	3		1	5	3	
	5	10	20						5.5	4	
	6		25						6		
	8								8		
	10								9		
	12		30	M4	4.6	3.75			10	5	0.5
	13										
	15	10	34					1.5	11.5	6	
	16		35						12		
	20		40	M5	5.6	4.5			14	7	
	25	12	45						17		
	30	15	55	M6	6.7	6			20	10	
	35		60						23	12	1
	40	18	70	M8	9.1	7		2	26	13	
	50	22	85	M10	11.1	9	3		32	16	